

**FUKUI**

**RGX-S Series**

## Contents

◆ Features .....	1
◆ Structure.....	1
◆ Cap Code .....	2
◆ Type code.....	2
◆ Cross-sectional View and Standard Materials .....	3
◆ Actual Area.....	4
◆ Pressure and temperature Rating.....	4
◆ Dimensions and Weight.....	4

## ◆ Features


The RGX-S series is a small, general-purpose lift-type pressure relief valve with a screw-in connection. The body material is bronze casting, and the main parts and spring are made of stainless steel.

It is mainly applicable to the High-Pressure Gas Safety Act and has a proven track record as a high-pressure gas certified valve.


## ◆ Structure

The RGX-S has a simplified structure with the body and bonnet being made as a single piece of casting.


- ◆ Full nozzle
- ◆ With adjusting ring
- ◆ Cast integral body and bonnet



Cap Code



(A) Closed screwed cap




(B) Closed screwed cap + test gag



Type code

RGX-S	(A)	
	Cap Code	
	(A)	Closed screwed cap
	(B)	Closed screwed cap + Test Gag

# 



No.	Part Name	Material
1	Body	CAC406
2	Cap	CAC406C
3	Nozzle	SUS304
4	Disc	SUS304
5	Disc holder	CAC406C
6	Spindle	SUS304
7	Adjusting ring	CAC406C
8	Adjusting ring lock bolt	CAC406C
9	Lower lock bolt	CAC406C
10	Spring	SUS304
11	Spring washer	CAC406C
12	Adjusting screw	CAC406C
13	Adjusting screw Lock Nut	CAC406C
14	Gasket (cap)	V 7020
15	Gasket	V 7020


### ◆ Actual Area

size	Seat diameter mm	Area mm <sup>2</sup>	Nominal lift mm
3/4*12*3/4	12	30.1	0.8
1*19*1	19	77.59	1.3

### ◆ Pressure and temperature Rating

size	Temperature °C		Maximum pressure MPa
	Minimum	Maximum	
3/4*12*3/4	- 196	200	3.5
1*19*1			

### ◆ Dimensions and Weight



Dimensions and weight						Unit: mm , kg	
Size	Connection		Center to face		Approx. Hight	Wrench Width	Approx. Weight
	M	FM	H1	L	H	W	
3 /4*12*3/4	R 3/4	RP3/4	65	40	170	32	1.2
1 *19*1	R1	RP 1	75	45	208	38	1.8



**Head Office Hirakata Plant**

1-6 Shodaitajika, Hirakata, Osaka 573-1132, Japan

TEL +81-72-857-4521 FAX +81-72-857-3764

E-mail: fki@fkis.co.jp

**Global Marketing**

1-6 Shodaitajika, Hirakata, Osaka 573-1132, Japan

**Overseas**

TEL +81-72-857-4527 FAX +81-72-857-3324

E-mail: stm@fkis.co.jp

**Domestic**

TEL +81-72-857-5501

FAX +81-72-857-5502

E-mail: osk@fkis.co.jp

**Yokohama Office**

Wesport Bldg 10th Floor, 2-6-32, Takashima, Nishi-ku,  
Yokohama-shi, Kanagawa, Japan

zip 220-0011

TEL +81-45-441-4411 FAX +81-45-441-0031

E-mail: ybm@fkis.co.jp

**FUKUI SEISAKUSHO CO., LTD.**

The product photos and structures are representative examples. Product specifications in the catalog may be changed without notice for product improvement or quality enhancement.